

Pattern Generation by Cellular Automata* (Invited Talk)

Jarkko Kari

Department of Mathematics and Statistics
FI-20014 University of Turku, Finland
jkari@utu.fi

Abstract

A one-dimensional cellular automaton is a discrete dynamical system where a sequence of symbols evolves synchronously according to a local update rule. We discuss simple update rules that make the automaton perform multiplications of numbers by a constant. If the constant and the number base are selected suitably the automaton becomes a universal pattern generator: all finite strings over its state alphabet appear from a finite seed. In particular we consider the automata that multiply by constants 3 and $3/2$ in base 6. We discuss the connections of these automata to some difficult open questions in number theory, and we pose several further questions concerning pattern generation in cellular automata.

1998 ACM Subject Classification F.1.1 Models of Computation

Keywords and phrases cellular automata, pattern generation, Z-numbers

Digital Object Identifier 10.4230/LIPIcs.RTA.2013.1

1 Enumerating all patterns by a cellular automaton

Cellular Automata (CA) are parallel and synchronous rewrite systems with local dependencies. The system consists of a regular grid of *cells*, each storing a single symbol called the *state* of the cell. The cells change their states synchronously according to a *local update rule* that specifies the new state depending on the local pattern of states around the cell. As cellular automata obey fundamental principles of physics such as locality and uniformity in space and time, they have found applications in various modeling situations of natural systems [2].

Cellular automata were first introduced by John von Neumann, following a suggestion by Stanislaw Ulam, to demonstrate an abstract universal constructor in an artificial setting [9]. Since then, the complexity that can arise from simple local rules and simple seed patterns has been demonstrated several times. Most notably, the well-known *Game-of-Life* cellular automaton by John Conway supports universal computation [1], as does *Rule 110*, a one-dimensional cellular automaton with binary alphabet and radius-one local update rule [3].

In this talk we consider a question asked by Stanislaw Ulam about generating all patterns from a single finite seed [8, page 30]. The problem is to design a cellular automaton rule and an initial configuration with all but finitely many cells in null states such that in the evolution that follows all finite patterns over the state alphabet will appear. We use two simple facts to design such a rule [6]: (i) the powers of a number n written in base b contain all finite digit sequences if n is not a rational power of b , and (ii) the multiplication of numbers by n in base b is a cellular automaton if all prime factors of n also divide b . Smallest such example

* Research supported by the Academy of Finland Grant 131558.



© Jarkko Kari;

licensed under Creative Commons License CC-BY

24th International Conference on Rewriting Techniques and Applications (RTA'13).

Editor: Femke van Raamsdonk; pp. 1–3

Leibniz International Proceedings in Informatics



Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany



simulate the Collatz-function

$$m \mapsto \begin{cases} m/2, & m \text{ even,} \\ 3m + 1, & m \text{ odd,} \end{cases}$$

on base 6 representations of positive integers [5].

References

- 1 E.R. Berlekamp, J.H. Conway, and R.K. Guy. *Winning ways for your mathematical plays, Volume 2: Games in Particular*. Academic Press, 1982.
- 2 B. Chopard and M. Droz. *Cellular automata modeling of physical systems*. Cambridge University Press, 1998.
- 3 M. Cook. Universality in Elementary Cellular Automata. *Complex Systems*, 15(1):1–40, 2004.
- 4 J. Kari. Theory of cellular automata: A survey. *Theor. Comput. Sci.*, 334(1-3):3–33, 2005.
- 5 J. Kari. Cellular automata, the collatz conjecture and powers of 3/2. In H.-C. Yen and O. Ibarra, editors, *Developments in Language Theory*, volume 7410 of *Lecture Notes in Computer Science*, pages 40–49. Springer, 2012.
- 6 J. Kari. Universal pattern generation by cellular automata. *Theoretical Computer Science*, 429(0):180 – 184, 2012.
- 7 K. Mahler. An unsolved problem on the powers of 3/2. *Journal of The Australian Mathematical Society*, 8:313–321, 1968.
- 8 S.M. Ulam. *A Collection of Mathematical Problems*. Interscience, New York, NY, USA, 1960.
- 9 J. von Neuman. *The Theory of Self-Replicating Automata (Ed. Burks, A. W.)*. University of Illinois Press, Urbana, IL, 1966.