

# Shortest Superstring

Marcin Mucha

University of Warsaw, Warsaw, Poland

---

## Abstract

In the *Shortest Superstring* problem (SS) one has to find a shortest string  $s$  containing given strings  $s_1, \dots, s_n$  as substrings. The problem is NP-hard, so a natural question is that of its approximability.

One natural approach to approximately solving SS is the following *GREEDY* heuristic: repeatedly merge two strings with the largest overlap until only a single string is left. This heuristic is conjectured to be a 2-approximation, but even after 30 years since the conjecture has been posed, we are still very far from proving it. The situation is better for non-greedy approximation algorithms, where several approaches yielding 2.5-approximation (and better) are known.

In this talk, we will survey the main results in the area, focusing on the fundamental ideas and intuitions.

**1998 ACM Subject Classification** F.2.2 Nonnumerical Algorithms and Problems

**Keywords and phrases** shortest superstring, approximation algorithms

**Digital Object Identifier** 10.4230/LIPIcs.CPM.2017.3

**Category** Invited Talk



© Marcin Mucha;

licensed under Creative Commons License CC-BY

28th Annual Symposium on Combinatorial Pattern Matching (CPM 2017).

Editors: Juha Kärkkäinen, Jakub Radoszewski, and Wojciech Rytter; Article No. 3; pp. 3:1–3:1

Leibniz International Proceedings in Informatics



LIPIC Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany