

Ontology-Based Data Access and Constraint Satisfaction

Frank Wolter

University of Liverpool, Department of Computer Science
Ashton Building, United Kingdom
wolter@liverpool.ac.uk

Abstract

In recent years, the use of ontologies (=logical theories) to access instance data has become increasingly popular. The general idea is that an ontology provides a vocabulary or conceptual model for the application domain, which can then be used as an interface for querying instance data and to derive additional facts [2, 6].

In this presentation, I will introduce ontology-based data access for ontologies given in description logics and investigate the following non-uniform complexity problem: what is the data complexity of conjunctive query answering for a fixed ontology? I will present general conditions under which this problem is in PTime and, respectively, coNP-hard. Then it is shown that for the basic description logic \mathcal{ALC} (=modal logic), conjunctive query answering is equivalent to solving constraint satisfaction problems with finite templates. Examples of consequences of this result include: (i) a P/coNP dichotomy holds for conjunctive query answering with \mathcal{ALC} if, and only if, Feder and Vardi's dichotomy conjecture [3] for constraints satisfaction problems holds; (ii) first-order constraint satisfaction problems investigated and characterized in [4] correspond exactly to reductions of ontology based data access with \mathcal{ALC} to standard query answering over relational databases known as FO-rewriting.

By employing results from [1], we also show that if functional relations are added to \mathcal{ALC} , then the word problem of every non-deterministic polynomial time Turing Machine can be reduced to conjunctive query answering. Thus, by Ladner's Theorem, ontologies with coNP-intermediate conjunctive query answering exist.

The talk is based on joint work with Carsten Lutz. Preliminary results are published in [5].

1998 ACM Subject Classification F.4.1 Computational Logic

Digital Object Identifier 10.4230/LIPIcs.CSL.2011.4

References

- 1 F. Baader, M. Bienvenu, C. Lutz, and F. Wolter. *Query and predicate emptiness in description logics*. Proceedings of the Twelfth International Conference on the Principles of Knowledge Representation and Reasoning (KR), 2010.
- 2 D. Calvanese, G. De Giacomo, D. Lembo, M. Lenzerini, and R. Rosati. *Tractable reasoning and efficient query answering in description logics: The DL-Lite family*. Journal of Automated Reasoning, 39(3):385–429, 2007.
- 3 T. Feder and M. Y. Vardi. *Monotone monadic SNP and Constraint Satisfaction*. STOC, pages 612–622, 1993
- 4 B. Larose, C. Loten, and C. Tardif. *A characterisation of first-order constraint satisfaction problems*. Logical Methods in Computer Science, 3(4), 2007.
- 5 C. Lutz and F. Wolter. *Non-Uniform Data Complexity of Query Answering in Description Logics*. Proceedings of Description Logic Workshop, CEUR Workshop Proceedings, 2011
- 6 C. Lutz, D. Toman, F. Wolter. *Conjunctive Query Answering in the Description Logic EL Using a Relational Database System*. Proceedings of IJCAI, pages 2070–2075, 2009.



© Frank Wolter;
licensed under Creative Commons License NC-ND
Computer Science Logic 2011 (CSL'11).

Editor: Marc Bezem; pp. 4–4



Leibniz International Proceedings in Informatics
LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany